

# HOOLOGUN 300



## CHASSIS

<b>Front Suspension:</b>	Φ54 × Φ60 - 940mm Inverted Hydraulic Dual Adjustable Forks
<b>Rear Suspension:</b>	Fully Adjustable Single Spring Shock
<b>Front Brake:</b>	Dual Piston Caliper, 260 mm Disc
<b>Rear Brake:</b>	Single Piston Caliper, 240 mm Disc
<b>Front Tire:</b>	80/100 - 21
<b>Rear Tire:</b>	110/90 - 18

## DIMENSION/CAPACITIES

<b>L × W × H:</b>	2260 × 870 × 1260 mm
<b>Seat Height:</b>	940 mm
<b>Wheelbase:</b>	1500 mm
<b>Min. Ground Clearance:</b>	275 mm
<b>Max. Permissionable Weight:</b>	200 kg
<b>Rider Capacity:</b>	One Person
<b>Curb Weight:</b>	130 kg
<b>Engine Oil:</b>	1.2 L
<b>Fuel Tank Capacity:</b>	9 L
<b>Battery:</b>	12V - 5Ah - Lithium Battery

## TECHNICAL SPECIFICATION

## ENGINE

<b>Engine Type:</b>	NC298 Single Cylinder, 4-Stroke, 4-Valve, Liquid Cooled, SOHC, Balance Shaft
<b>Displacement:</b>	298 ml
<b>Bore × Stroke:</b>	84 × 53.6 mm
<b>Compression Ratio:</b>	11.6:1
<b>Max. Power:</b>	19.5/9000 kW/rpm
<b>Max. Torque:</b>	23.5/7000 N.m/rpm
<b>Max. Speed:</b>	120 km/h
<b>Lubrication:</b>	Pressure, splash
<b>Clutch Type:</b>	Manual Wet Multi-plate
<b>Ignition:</b>	Pointless Electronic Ignition PEI
<b>Starting System:</b>	Electric
<b>Fuel System:</b>	Electronic Fuel Injection EFI
<b>Transmission System:</b>	Chain drive, International Gear Pattern, 6-Speed

