

# HOOLOGUN 450



## CHASSIS

<b>Front Suspension:</b>	Φ54 × Φ60 - 940mm Inverted Hydraulic Dual Adjustable Forks
<b>Rear Suspension:</b>	Fully Adjustable Single Spring Shock
<b>Front Brake:</b>	Dual Piston Caliper, 260 mm Disc
<b>Rear Brake:</b>	Single Piston Caliper, 240 mm Disc
<b>Front Tire:</b>	80/100 - 21
<b>Rear Tire:</b>	100/90 - 18

## DIMENSION / CAPACITIES

<b>L × W × H:</b>	2170 × 825 × 1270 mm
<b>Seat Height:</b>	950 mm
<b>Wheelbase:</b>	1500 mm
<b>Min. Ground Clearance:</b>	320 mm
<b>Max. Permissionable Weight:</b>	200 kg
<b>Rider Capacity:</b>	One Person
<b>Dry Weight:</b>	119 kg
<b>Engine Oil:</b>	1.2 L
<b>Fuel Tank Capacity:</b>	11 L
<b>Battery:</b>	12V - 7Ah - Lithium Battery

## TECHNICAL SPECIFICATION

## ENGINE

<b>Engine Type:</b>	Single cylinder, 4-stroke, 4-valve, liquid-cooled, SOHC, balance shaft
<b>Displacement:</b>	449 ml
<b>Bore × Stroke:</b>	94.5 × 64 mm
<b>Compression Ratio:</b>	10.8:1
<b>Max. Power:</b>	35/9000 kW/rpm
<b>Max. Torque:</b>	40/7000 Nm/rpm
<b>Max. Speed:</b>	≥120 km/h
<b>Lubrication:</b>	Pressure, splash
<b>Clutch Type:</b>	Manual Wet Multi-plate
<b>Ignition:</b>	Digital CDI
<b>Starting System:</b>	Electric
<b>Fuel System:</b>	Electronic Fuel Injection EFI
<b>Transmission System:</b>	Chain drive, International Gear Pattern, 6-Speed

