

MUTINY 250



TECHNICAL SPECIFICATION

CHASSIS

Front Suspension:	Upside Down Shocks
Rear Suspension:	Single Spring Shock
Front Brake:	Hydraulic twin piston Disc Brake
Rear Brake:	Hydraulic single piston Disc Brake
Front Tire:	90/90 - 19
Rear Tire:	110/90 - 17

DIMENSION/CAPACITIES

L x W x H:	2080 x 860 x 1270 mm
Seat Height:	845 mm
Wheelbase:	1365 mm
Turning Radius:	2365 mm
Min. Ground Clearance:	260 mm
Max. Permissionable Weight:	150 kg
Rider Capacity:	2 Persons
Dry Weight:	127 kg
Engine Oil:	1.1 L
Fuel Tank Capacity:	15 L
Battery:	12V - 6.5Ah

ENGINE

Engine Type:	Single cylinder, 4-stroke, oil-cooled, SOHC, counterbalancer shaft
Displacement:	232 ml
Bore x Stroke:	69 x 75.85 mm
Compression Ratio:	9:1
Max. Power:	13.0/7000 kW/rpm
Max. Torque:	19.0/5500 Nm/rpm
Max. Speed:	≥110 km/h
Lubrication:	Pressure, splash
Clutch Type:	Multiplate wet clutch
Ignition:	DCDI
Starting System:	Electric/Kick
Fuel System:	Caburetor
Transmission System:	Chain drive, 5 gears

