

# MUTINY 400



## TECHNICAL SPECIFICATION

### CHASSIS

<b>Front Suspension:</b>	Upside Down Shocks
<b>Rear Suspension:</b>	Single Spring Shock
<b>Front Brake:</b>	Hydraulic twin piston Disc Brake
<b>Rear Brake:</b>	Hydraulic single piston Disc Brake
<b>Front Tire:</b>	100/90 - 19
<b>Rear Tire:</b>	130/80 - 17

### DIMENSION/CAPACITIES

<b>L x W x H:</b>	2080 x 870 x 1360 mm
<b>Seat Height:</b>	850 mm
<b>Wheelbase:</b>	1400 mm
<b>Turning Radius:</b>	2365 mm
<b>Min. Ground Clearance:</b>	240 mm
<b>Max. Permissionable Weight:</b>	150 kg
<b>Rider Capacity:</b>	2 Persons
<b>Dry Weight:</b>	151 kg
<b>Engine Oil:</b>	2.1 L
<b>Fuel Tank Capacity:</b>	16 L
<b>Battery:</b>	12V - 6.5Ah

### ENGINE

<b>Engine Type:</b>	Single cylinder, 4-stroke, oil-cooled, DOHC, 4 valves, counterbalancer shaft
<b>Displacement:</b>	397.2 ml
<b>Bore x Stroke:</b>	85 x 70 mm
<b>Compression Ratio:</b>	8.8:1
<b>Max. Power:</b>	19.5/7000 kW/rpm
<b>Max. Torque:</b>	30.0/5500 Nm/rpm
<b>Max. Speed:</b>	≥140 km/h
<b>Lubrication:</b>	Pressure, splash
<b>Clutch Type:</b>	Multiplate wet clutch
<b>Ignition:</b>	DCDI
<b>Starting System:</b>	Electric/Kick
<b>Fuel System:</b>	Caburetor
<b>Transmission System:</b>	Chain drive, 6 gears

